

# level

## Product Specifications: IMO Vinyl Wallcovering

---

### Physical Properties

**DESCRIPTION**.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering  
**CONSTRUCTION**.....Osnaburg Backed Embossed PVC-Vinyl with UV-LED Inks and UV Matte Coating

#### SUBSTRATE

Roll Width .....54" (1.37 m)  
Weight .....20 oz. per lineal yard  
Face .....Textured PVC-Vinyl  
Backing .....Polyester/Cotton Osnaburg

#### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

#### OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

---

### Flame & Smoke

ASTM-E84 ..... Class A  
NFPA 286 Corner Burn Test, Class A  
CAN S102M Tunnel Test, Class A  
EU Classification in accordance with EN 13501  
ASTM E603, Early Warning Effect® Life Safety and Property Protection

---

### Mold & Mildew

ASTM G21 ..... Passed requirements

---

### Specifications

Federal Specifications  
GSA CCC-408A, Type II, Class A  
WA Specifications  
WA-101, Type II, Class A  
NFPA 101 Life Safety Code  
Meets requirements, NFPA 225, Class A  
Interior Finish, IMO  
Meets IMO FTP-Code, Annex 1, Parts 2 and 5

---

### Environmental

Cadmium and Heavy Metal-free  
Compliant with CHPS Section 01350  
EU Toxicity compliant for EN 12149

---