

level

Product Specifications: Smooth Silver Vinyl Wallcoverings

Physical Properties

DESCRIPTION.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering
CONSTRUCTION.....Nonwoven-Backed Smooth Silver PVC-Vinyl with UV-LED Inks and UV Matte coating

SUBSTRATE

Roll Width54" (1.37 m)
Weight20 oz. per lineal yard
FaceSmooth Silver Mylar/PVC-Vinyl
BackingNonwoven

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A

Mold and Mildew

ASTM G21 Passed requirements

Washability and Scrubability

ASTM F793 Standard Classification of Wallcovering by Characteristics
Washability para. 7.4, 100 cycles: Passed all requirements
Scrubability para. 7.7, 300 cycles: Passed all requirements

level

Specifications

Federal Specifications:

GSA CCCW-408-D, Type II, Passed requirements

WA Specifications:

WA-101, Type II, Passed requirements

NSF/ANSI-342, Certified for Silver compliance

NFPA Life Safety Code 101

Passes all requirements for smoke and flame

Environmental

Low-VOC

EU Toxicity compliant

California Prop 65 compliant

Phthalate free, Cadmium and Lead-Free

100% of backing fiber content is Post-Consumer

11% Post-Consumer content in total product using recycled polyester and cellulose