

level

Product Specifications: Textured Carta PVC-Free Wallcovering

Physical Properties

DESCRIPTION.....Type II, 14 oz. Eco-Friendly PVC-Free Wallcovering
CONSTRUCTION.....Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks and UV Matte Coating

SUBSTRATE

Roll Width54" (1.37 m)
Weight14 oz. per lineal yard (22 mil)
FacePolyester/Natural Fiber Technology
BackingNonwoven 31% Post-Consumer Recycled Content

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A
CAN/ULC-S102.2 Passed requirements

Mold and Mildew

ASTM E96 Permeability, 66 Perms Dry Cup Method, Passed WA-101 8 Perms

Specifications

WA Specifications:
WA-101, Type II, Passed requirements
NSF/ANSI-342, Certified for Silver compliance

Environmental

Low-VOC
Prop 65 Compliant
Compliant with CHPS Section 01350
Recycled Content, 31% Post-Consumer
Free of PVC and POA (Olefin) Plasticizers, Phthalates, formaldehyde, Chlorine, Halogen, Heavy-Metals (Cadmium, Mercury, Lead, Zinc) Ozone Depleting Chemicals and Brominated flame retardants

level

LEED Eligibility

Product may contribute up to 2 LEED credits, conditionally, 2 other credits

MR Credit 4.1 Recycled Content 20%

MR Credit 4.2 Recycled Content 30%

Conditionally

MR Credit 2.1 Contribution to project recycling program

MR Credit 2.2 Contribution to project recycling program

MR Credit 5.1 Manufactured local to new construction

EQ Credit 4.1 Mounted with low emitting adhesives