

level

Product Specifications: WallMax Liquid Laminate

Wherever applicable, Level products are coated with WallMax, our protective liquid laminate, and we highly recommend its use on customized products as well.

This UV curable coating provides important stain resistance to common concerns in high-traffic commercial environments.

WallMax contains fire suppressing chemistry and has been tested and proven to contribute towards achieving Class A fire ratings through ASTM-E84 test methods.

The coating formulation is heavy metal free with attributes that have been tested and proven to kill bacteria and prevent mold spores from forming, even in the most humid environments.

WallMax is not recommended for use over Spot Gloss inks though, as it will nullify the gloss effect.

Flame & Smoke

WHEN APPLIED TO STIPPLE VINYL

ASTM-E84 Class A Fire Rated
Flame Spread..... 25
Smoke Developed 140
EU Class Flame (EN15102), B-s1
CAN/ULC-S102.2: Passed requirements
BS476 Parts 6&7: Passed requirements
Federal Specifications: GSA CCC-408-D, Type II
WA Specifications: WA-101, Type II / NSF/ANSI-342, Certified for Silver compliance
NFPA Life Safety Code 101: Passed requirements for flame and smoke

Washability & Scrubability

WHEN APPLIED TO STIPPLE VINYL

ASTM F793 Standard Classification of Wallcovering by Characteristics
Washability para. 7.4, 100 cycles: Passed all requirements
Scrubability para. 7.7, 300 cycles: Passed all requirements

Mold & Mildew

WHEN APPLIED TO STIPPLE VINYL

ASTM-G21 Passed Requirements