

level

Product Specifications: Smooth Carta PVC-Free Wallcovering Printed on HP PVC-Free Durable Wall Paper

Physical Properties

DESCRIPTION.....Type II, 17 mil Eco-Friendly PVC-Free Wallcovering
CONSTRUCTION.....Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks

SUBSTRATE

Roll Width54" (1.37 m)
Weight290 g/m² per TAPPI T-410 Test Method
FaceLatex-Saturated Wet-Strength Paper
BackingTextile Scrim

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A Fire Rated
Compliant with California Fire Code CA 1237
Compliant with IBC (International Building Code) sec. 803.1.1

Mold and Mildew

Highly Resistant – GREENGUARD Test method, GGTM.P040 per guidelines of ASTM D6329

Specifications

EN233 – Spongeability rating (wave 1), Excellent color fastness rating
Carries the CE certification according to European Standard EN15102.

Environmental

REACH compliant
FSC®-certified paper
Compliant with CHPS Section 01350
