

level

Product Specifications: Stipple Vinyl Wallcovering

Physical Properties

DESCRIPTION.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering

CONSTRUCTION.....Osnaburg Backed Textured Vinyl with UV-LED Inks and UV Matte coating

SUBSTRATE

Roll Width54" (1.37 m)

Weight20 oz. per lineal yard

FaceStipple Embossed PVC-Vinyl

BackingOsnaburg

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

SUBSTRATE

ASTM-E84 Class A

NFPA 101 Life Safety..... Class A

NFPA 286 Corner Burn..... Passed requirements

CAN/ULC-S102.2 Passed requirements

Performance

Low VOC, California Section 01350 IAQ

Recycled content

Non-Phthalate

NSF/ANSI 342 Certified

EPD/HPD

California Prop 65, No Labeling Required

Anti-Microbial Protection

- Does not support growth of bacteria, viruses or fungi
 - ASTM G21, G22, and E1428
-