

level

Product Specifications: Targa Sheet Adhesives & Caulk

Product Details

The combination of our approved primer, adhesive, and caulk allows for easy, cost-effective and secure installations of Targa panels, with the cured product exhibiting excellent adhesion and color retention. All products are nonflammable and freeze-thaw stable.

HEAVY-DUTY WATER MASTIC ADHESIVE

- High-strength adhesive
- Aggressive initial tack and permanent flexible bond
- Synthetic latex base
- Contains integrated antimicrobial agents

WATER-BASED MASTIC PRIMER

- Designed for sealing and priming wallboard and concrete block
- Allows wall covering to be shifted or repositioned during the installation
- Butadiene resin base
- Inhibits polyvinyl acetate

COLORFLEX II CAULK

- Can be used to seal miter joints and caulk vertical and horizontal joints/corners
- Able to withstand intermittent water, but will not withstand water immersion
- Cured product remains flexible and color stable in non-UV interior conditions
- Acrylic latex base
- Available in clear or color-matched caulk

Certifications & Testing

HEAVY-DUTY WATER MASTIC ADHESIVE

- Mildew & stain resistant
- Meets class A/1 fire rating per ASTM E-84 for .075" or thinner gauge sheets
- Meets restricted-use rating per CAN / ULC-S102.2 for .060" or thinner gauge sheets
- Meets California Department of Public Health CDPH /EHLB /standard method version 1.1.2010 (emission testing method for CA specification 01350)

COLORFLEX II CAULK

- Resistant to certain bacterial & fungal growth (per ASTM G 22-76 and G 21-13)
- Meets the performance specifications of ASTM-C834 for latex sealants
- Cured ColorFlex II ® has a Shore A value of greater than 55 (product considered "pick-resistant" based on industry standards); testing conducted by independent lab in accordance with ASTM C661 and ASTM C920