

level

Product Specifications: Type III Vinyl Linen Emboss Wallcoverings

Physical Properties

DESCRIPTION.....Type III 35 oz. PVC-Vinyl Wallcovering

CONSTRUCTION.....Woven-Backed Textured Vinyl Printed with UV-LED Inks

SUBSTRATE

Roll Width54" (1.37 m)

Weight35 oz. per lineal yard

FaceTextured PVC-Vinyl

BackingWoven Poly-Cotton

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Type III Properties

Passes all criteria for WA101 Type III properties including:

Break Strength

Tear Strength

Cold Crack

Heat Aging

Shrinkage

Stain Resistance

Coating Adhesion

Colorfastness

Washability

Scrubability

Blocking

Crocking

Flame & Smoke

SUBSTRATE

ASTM-E84 Class A

Mold & Mildew Resistance

ASTM-G21 Score of 0 @ Week 3

Impact Resistance

ASTM-D5420 Passed with 74.22 lb.

Environmental

Air Quality Meets California Section IAQ 1350

No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen

No Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals

Prop 65 Compliant

No Harmful Off-Gassing

Low VOC Emitting
