

level

Product Specifications: IMO Vinyl Wallcovering

Physical Properties

DESCRIPTION.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering
CONSTRUCTION.....Osnaburg Backed Embossed PVC-Vinyl with UV-LED Inks

SUBSTRATE

Roll Width54" (1.37 m)
Weight20 oz. per lineal yard
FaceTextured PVC-Vinyl
BackingPolyester/Cotton Osnaburg

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A
NFPA 286 Corner Burn Test, Class A
CAN S102M Tunnel Test, Class A
EU Classification in accordance with EN 13501
ASTM E603, Early Warning Effect® Life Safety and Property Protection

Mold & Mildew

ASTM G21 Passed requirements

Specifications

Federal Specifications
GSA CCC-408A, Type II, Class A
WA Specifications
WA-101, Type II, Class A
NFPA 101 Life Safety Code
Meets requirements, NFPA 225, Class A
Interior Finish, IMO
Meets IMO FTP-Code, Annex 1, Parts 2 and 5

Environmental

Cadmium and Heavy Metal-free
Compliant with CHPS Section 01350
EU Toxicity compliant for EN 12149
