

# level

## Product Specifications: Smooth Silver Vinyl Wallcoverings

---

### Physical Properties

**DESCRIPTION**.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering

**CONSTRUCTION**.....Nonwoven-Backed Smooth Silver PVC-Vinyl with UV-LED

#### **SUBSTRATE**

Roll Width .....54" (1.37 m)

Weight .....20 oz. per lineal yard

Face .....Smooth Silver Mylar/PVC-Vinyl

Backing .....Nonwoven

#### **INKS**

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

#### **OPTIONAL WALLMAX COATING**

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

---

### Flame & Smoke

ASTM-E84 ..... Class A

---

### Mold and Mildew

ASTM G21 ..... Passed requirements

---

### Washability and Scrubability

ASTM F793 Standard Classification of Wallcovering by Characteristics

Washability para. 7.4, 100 cycles: Passed all requirements

Scrubability para. 7.7, 300 cycles: Passed all requirements

# level

---

## Specifications

### Federal Specifications:

GSA CCCW-408-D, Type II, Passed requirements

### WA Specifications:

WA-101, Type II, Passed requirements

NSF/ANSI-342, Certified for Silver compliance

### NFPA Life Safety Code 101

Passes all requirements for smoke and flame

---

## Environmental

Low-VOC

EU Toxicity compliant

California Prop 65 compliant

Phthalate free, Cadmium and Lead-Free

100% of backing fiber content is Post-Consumer

11% Post-Consumer content in total product using recycled polyester and cellulose