

level

Product Specifications: Stipple Vinyl Wallcovering

Physical Properties	DESCRIPTION Category V, Type II 20 oz. PVC-Vinyl Wallcovering
	CONSTRUCTION Woven Backed Textured Vinyl Printed with UV-LED Inks
	SUBSTRATE
	Roll Width 54" (1.37 m)
	Weight 20 oz. per lineal yard
	Face Embossed PVC-Vinyl
	Backing Polyester/Cotton Osnaburg
	INKS
	UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.
	OPTIONAL WALLMAX COATING
	Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke	ASTM-E84 Class A	EU Class Flame (EN15102), B-s1
	Flame Spread 25	CAN/ULC-S102.2 Passed requirements
	Smoke Developed..... 140	BS476 Parts 6&7 Passed requirements

Mold & Mildew	ASTM G21 Passed requirements
---------------	------------------------------------

Washability & Scrubability	ASTM F793 Standard Classification of Wallcovering by Characteristics
	Washability para. 7.4, 100 cycles: Passed all requirements
	Scrubability para. 7.7, 300 cycles: Passed all requirements

Specifications	Federal Specifications:
	GSA CCC-408-D, Type II
	WA Specifications:
	WA-101, Type II
	NSF/ANSI-342, Certified for Silver compliance NFPA Life Safety Code 101

Environmental	Low-VOC
	EU Toxicity compliant
	California Prop 65 compliant
	Phthalate free, Cadmium and Lead-Free
