

Product Specifications: Targa Sheet Adhesives & Caulk



Product Details

The combination of our approved primer, adhesive, and caulk allows for easy, cost-effective and secure installations of Targa panels, with the cured product exhibiting excellent adhesion and color retention All products are nonflammable and freeze-thaw stable.

HEAVY-DUTY WATER MASTIC ADHESIVE

High-strength adhesive

Aggressive initial tack and permanent flexible bond

Synthetic latex base

Contains integrated antimicrobial agents

WATER-BASED MASTIC PRIMER

Designed for sealing and priming wallboard and concrete block

Allows wall covering to be shifted or repositioned during the installation

Butadiene resin base

Inhibits polyvinyl acetate

COLORFLEX II CAULK

Can be used to seal miter joints and caulk vertical and horizontal joints/corners

Able to withstand intermittent water, but will not withstand water immersion

Cured product remains flexible and color stable in non-UV interior conditions

Acrylic latex base

Available in clear or color-matched caulk

Certifications & Testing

HEAVY-DUTY WATER MASTIC ADHESIVE

Mildew & stain resistant

Meets class A/1 fire rating per ASTM E-84 for .075" or thinner gauge sheets

Meets restricted-use rating per CAN / ULC-S102.2 for .060" or thinner gauge sheets

Meets California Department of Public Health CDPH /EHLB /standard method version1.1.2010 (emission testing method for CA specification 01350)

COLORFLEX II CAULK

Resistant to certain bacterial & fungal growth (per ASTM G 22-76 and G 21-13)

Meets the performance specifications of ASTM-C834 for latex sealants

Cured ColorFlex II ® has a Shore A value of greater than 55 (product considered "pick-resistant" based on industry standards); testing conducted by independent lab in accordance with ASTM C661 and ASTM C920